

Thermocord PIC



FEATURES:

- Exceptional effective fire detection cable
- 100% Waterresistant (except ends)
- Uniquely easy to install and maintain
- Compatible with all DSPA Generator types

Description

The DSPA Thermocord PIC can be used as part of a highly effective fixed extinguishing system. A thermocord PIC is installed to a DSPA Generator and can be used for the detection of fire and the activation of the DSPA generator. The DSPA Thermocord PIC in combination with a DSPA generator are effective on class A, B, C fires.

Application

The DSPA Thermocord PIC is recommended for the protection of objects and narrow compartments under moisture conditions, such as engine compartments, electrical cabinets, switchgears and cable ducts.

Specifications

Model	Thermocord
Part Number	100175
Colour	Red
Length	Per meter
Diameter	2 mm
Burning time	28.5 mm/sec.
Ignition temperature	165 °C
Shelflife	15 Years
Dangerous goods classification	1.4 G / UN nr. 0066 / Cord, igniter
Storage	The storage needs to be approved according national legislation. The thermocord PIC must only be stored in its original packing in a dry and cool environment.
Notes for secure handling	The product can be activated by open fire, a spark, or by temperature. Protect from heat sources and direct sunlight. Open the packaging with care. Don't use any machinery nearby that may create sparks. Keep away from heat sources — don't smoke.

More information:

DSPA.nl
 Hogelandseweg 30
 6545 AC Nijmegen
 The Netherlands
 T. +31 (0) 24 35 22 573
 E info@dspa.nl